

Vitoject® 890



APPLICATION

- › chemical industry
- › laboratories
- › manufacturing of chemicals
- › printing industry
- › metal and plastics processing
- › recycling and waste disposal
- › fire brigades
- › cleaning and maintenance
- › etching

QUALITIES AND ADVANTAGES

- › very good protection against extremely aggressive and toxic chemicals
- › very high gas tightness
- › solvent-free by eco-friendly injection moulding process
- › excellent wearing comfort
- › very good temperature flexibility
- › material is highly resistant to ozone and sunlight (UV)



Article no.	890
Name	Vitoject® 890
Material	fluorocarbon rubber
Description	rolled edge, smooth, powdered
Length (mm)	340 -360
Total thickness (mm)	0,7 ± 0,1
Colour	black
Size	8, 9, 10, 11
Classification	category III



FEATURES

- › AQL < 0,65
- › manufactured by Vulkoject process technology
- › wide shape makes it possible to wear gloves underneath (heat protection)
- › after contamination with specific chemicals a reconditioning, special cleaning process, is possible (in agreement with the KCL-laboratory)
- › can be combined with chemical protective clothing
- › excellent low degradation
- › good resistance against polycyclic aromatic hydrocarbons (petrochemistry)

www.kcl.de
sales@kcl.de



by Honeywell

KCL GmbH

Industriepark Rhoen
 Am Kreuzacker 9
 36124 Eichenzell
 Germany
 Phone +49 6659 87-300
 Fax +49 6659 87-318