

#### QUICK-SWITCH® BOLT BAG Part # OSBOLT

# **Instruction Manual**



## Contents

- Important Notes
- 2 Applicable Safety Standards
- 2 Safety Information
- 3 Installation
- 4 Specifications and Materials
- 4 Maintenance

- × Do not throw instructions away.
- Read and understand instructions before using this equipment.



## **Important Notes**

- Inspect prior to use
- Replace if there is evidence of wear, the QBBOLT is exposed to a shock load, or if there is any doubt of the QSBOLT's integrity.
- Remove tools prior to installing to prevent injury during installation. Always be sure to replace tools into the pockets and do not suspend.
- User shall determine suitability for use for all intended applications.
- Always close bag when items are not in use.

# Safety Information

- ▲ Do not use near moving parts, mechanisms, running machinery, or rotating equipment.
- May contain electrically conductive materials.
- ▲ Do not alter product in any way from its original state.

# **Applicable Safety Standards**

Meets or exceeds:

ANSI / ISEA 121-2018



#### Installation

#### Step 1

After installing the QSBOLT bag on a compatible belt, tighten the cord lock the cord-lock to ensure no tools or loose items fall out.



#### Step 2

Secure cord by passing free end through d-ring at bottom edge of bag and back up to the snap hook at the top of the bag.







#### Step 3

Attach Quick- Switch® tethers can to the docks not to exceed the weight limit of each dock.



#### Step 4

Attach conventional tool tethers to side d-rings not to exceed the weight limit of each dock.





# **Specifications**

Max. Tool Weight:

Quick-Switch® Dock: 6 lb (2.7 kg)

D-Rings: 3 lb (1.4 kg)

Working Load Limit (Container): 25 lb (11.3 kg)

Max. Tether Length:

Quick-Switch® Dock: Tested as a system, no tether length.

D-Rings: 48" (1.2 m)

#### Materials

Nylon and stainless steel.

# Maintenance, Cleaning, and Storage

Clean with a damp cloth and mild soap, wipe off excess and thoroughly dry.

Store this product away from tools and other objects that could cause damage.

#### USA

607 East Sam Houston Parkway South Suite 800 Pasadena, TX 77503 800 466 6385

customer.service@guardianfall.com

#### IJК

New Road, Sheerness Kent ME12 1PZ United Kingdom +44 (0) 1795 580 333 enquiries@quardianfall.com CANADA

580 Notre Dame Avenue, Unit 16 Sudbury, ON P3C 5L2

800 466 6385

customer.service@guardianfall.com

WARRAWTY: Guardian warrants to Buyer that all products are free from defects in material, workmanship, and design (if a Supplieir-responsible design), however this warranty does not over conditions resulting from normal wear and the are, neglect, abuse, accident or otherwise. Guardian is of warranty apply for the lifetime of the products and are limited to the replacement of product only. This warranty is not transferable to any other Guardian service and does not apply to product that is resuld after having been put into service. No other person, firm, entity, or the like is authorized to assume or assign for Guardian any other liability in connection with the sale or use of Guardian sproduces. Turthermore, this warranty is void if any product is changed or altered in any way, or if the product is used in a manner other than for which it is intended. There are no implied warranties of merchantability or fitness for a particular purpose, which are specifically desclaimed.